



# OWENS FLOORING

*nature's beauty engineered for life*

## Signature Selection

### Walnut – Select Grade

Characteristic	Specification
<b>Bark pockets</b>	Not Allowed
<b>Burls, Tight</b>	Unlimited burls, except burls around knots must blend (no distractive color variation)
<b>Checks/Cracks, Honeycomb</b>	Allowed within piece, not on edges or ends. Width of crack nominal 1/8", not visible thru (plywood) Maximum 2" length crack. No honeycomb No collection or cluster of cracks
<b>Color Variation</b>	Unlimited color variations of heartwood and steamed sapwood allowed.
<b>Open Knots, Knot Holes</b>	Allowed up to 1/8" diameter opening when plywood not visible. Can be clustered. Star or broken knots allowed up to 3/4" diameter (dime size) open when plywood not visible. Unlimited quantity
<b>Knot, Sound, Tight</b>	Maximum nominal 3/8" diameter Not visible thru (plywood) Cluster allowed.
<b>Knot, Pin</b> (Max 1/8" dia. open or closed)	Unlimited open or closed pin knots. Can be clustered.
<b>Mineral Streaks</b>	Allowed
<b>Sapwood</b>	"Bright" sapwood (unsteamed) limited to 20% per piece. Unlimited steamed sapwood.
<b>Wormholes</b>	Wormholes open to maximum nominal 1/8" diameter allowed. Clustered wormholes allowed, maximum 1 lineal foot per piece. No worm crawls

This document is the property of Owens Flooring and may not be used in any form or for any purpose without written approval from Owens Flooring LLC